

**BENEFIT-COST ANALYSIS METHODOLOGY  
TOWN OF FAIRMONT  
HAPPY HILLS AND WALNUT STREET  
PUMP STATION RELOCATION(S)**

*SUBMITTED TO*

**FEMA BUILDING RESILIENT INFRASTRUCTURE AND  
COMMUNITIES GRANT PROGRAM**

Town of Fairmont, Robeson County, NC



**January 6, 2023**

## TABLE OF CONTENTS

|   |                                     |
|---|-------------------------------------|
| <b>LIST OF FIGURES</b> .....                          | <b>I</b>                            |
| <b>LIST OF APPENDICES</b> .....                       | <b>II</b>                           |
| <b>1.0 PROJECT OVERVIEW</b> .....                     | <b>1</b>                            |
| 1.1 Project Background .....                          | 1                                   |
| 1.2 Proposed Mitigation and Level of Protection ..... | 2                                   |
| <b>2.0 HISTORIC EVENTS</b> .....                      | <b>3</b>                            |
| <b>3.0 PROJECT AND MAINTENANCE COSTS</b> .....        | <b>5</b>                            |
| <b>4.0 PROJECT USEFUL LIFE</b> .....                  | <b>6</b>                            |
| <b>5.0 SERVICE POPULATION</b> .....                   | <b>7</b>                            |
| <b>6.0 EFFECTS OF FLOODING</b> .....                  | <b>8</b>                            |
| 6.1 Source of Flooding.....                           | 8                                   |
| 6.2 Determining Recurrence Intervals .....            | <b>Error! Bookmark not defined.</b> |
| 6.3 Service Impacts .....                             | 9                                   |
| <b>7.0 RESULTS</b> .....                              | <b>10</b>                           |

## LIST OF FIGURES

|   |           |
|---|-----------|
| <b>Figure 1.1 Pump Station Locations</b> .....                              | <b>1</b>  |
| <b>Figure 2.1 Happy Hills Pump Station During Hurricane Florence</b> .....  | <b>3</b>  |
| <b>Figure 2.2 North Walnut Pump Station During Hurricane Florence</b> ..... | <b>4</b>  |
| <b>Figure 3.1 Project and Maintenance Costs</b> .....                       | <b>5</b>  |
| <b>Figure 3.2 Funding Partner Breakdown Chart</b> .....                     | <b>5</b>  |
| <b>Figure 6.1 Collection System Impact During Flood Events</b> .....        | <b>8</b>  |
| <b>Figure 7.1 Pump Station Relocation Project Benefit-Cost Ratio</b> .....  | <b>10</b> |

## **LIST OF APPENDICES**

**Appendix A: Project Layout Maps**

**Appendix B: Benefit-Cost Analysis Toolkit Export**

**Appendix C: Flood Insurance Rate Maps**

**Appendix D: NOAA Point Precipitation Frequency Estimates and Data**

**Appendix E: FEMA 2009 BCA Reference Guide – Project Useful Life Table**

**Appendix F: Pump Station Service Area Map**

**Appendix G: Historic Photos of Damage at Pump Station Sites**

**Appendix H: Happy Hill Pump Station Record Drawings**

## 1.0 PROJECT OVERVIEW

This methodology report consists of information used to complete the benefit-cost analysis (BCA), using FEMA’s BCA toolkit, for the relocation of the Happy Hills and North Walnut Pump Stations in the Town of Fairmont. Relocation of these two pump stations away from the 100-year floodplain will save the Town of Fairmont valuable time, money, and resources. Determined from information entered into the BCA toolkit, the combined project and maintenance cost of the project is \$2,977,785 and the benefits provided to the Town are \$4,997,235. Resulting in a benefit-cost ratio of 1.68. Information provided to FEMA’s toolkit is broken down below to highlight the driving factors of this relocation project and how the Town of Fairmont will greatly benefit from this project.

### 1.1 Project Background

The proposed project includes the relocation of two pump stations (Happy Hills Pump Station and North Walnut Pump Station) in the Town of Fairmont. Both stations are located adjacent to Old Field Swamp and become inundated during significant storm events. The Happy Hills Pump Station is located on Leesville Road's northern side. This station will be relocated to the end of South McMillan Drive, moving the pump station east. The North Walnut Pump Station is currently located on the eastern side of North Walnut Street at its intersection with Eldorado Road. The station will be relocated to the western side of North Walnut Street and south of Eldorado Road. Both stations are currently located in the NC Flood Risk Information Systems (FRIS) designated 100-year floodplain, this project will relocate each pump station out of this designated area to grounds not susceptible to 100-year floodwaters. **Figure 1.1** below represents the coordinates of each pump station.

**Figure 1.1 Pump Station Locations**

| Pump Station Name         | Latitude  | Longitude  |
|---------------------------|-----------|------------|
| Happy Hills Pump Station  | 34.497236 | -79.103038 |
| North Walnut Pump Station | 34.510769 | -79.109301 |

The Happy Hills station is the older of the two being constructed in 1988, North Walnut station being later constructed in 2001. Both stations experienced flooding during Hurricanes Florence and Matthew as noted in the attached photographs. This flooding leads to extended service interruptions, damage to essential system components, and excessive amounts of extraneous flow entering the collection system which contributes to downstream sewer overflows. Useful life at each station has declined due to flood events causing failures to numerous components. During heavy rain events, these pump stations are typically completely underwater and inaccessible by Town staff. The relocation of the Happy Hill pump station will consist of modifications to the gravity sewers to direct flow to the new site, construction of a new 80 GPM pump station, and new forcemain piping to connect the new station to the existing forcemain.



The North Walnut pump station relocation will consist of similar work as the Happy Hill station and includes modifications to the gravity sewers to direct flow to the new site, construction of a new 180 GPM pump station, and new forcemain piping to connect the new station to the existing forcemain. The proposed project will relocate both stations to higher elevations outside the FRIS 100-year floodplain as well as providing additional measures of protection to the stations for flood events that exceed the 100-year level.

## **1.2 Proposed Mitigation and Level of Protection**

The Town of Fairmont will contract a qualified engineering and construction team to implement the proposed project. The proposed project will eliminate / greatly reduce the risk of the existing pump stations becoming inundated by future flood events. Relocation will protect the Town's collection system from series of downward spiraling events, causing failure to multiple components within both pump station sewersheds. Failure events consist of wastewater backing up into homes and businesses in the pump station service areas, as well as contaminants from wastewater being released into the surrounding environment at the two pump stations. This will be completed by locating the new pump stations on high ground outside of the 100-year floodplain, elevating rim elevations to at least 2' above the 100-year flood elevation per NCDEQ minimum design standards, using submersible pumps to eliminate damage potential, and protecting electrical equipment from flood effects. These aspects of the proposed project will allow the system to continue operation during emergency conditions, prevent damage to existing components, reduce the potential for downstream sanitary sewer overflows, and improve water quality in the pump station service areas.

Proposed action will relocate and elevate pump stations to a height that allows for continued use in the event of similar floodwater catastrophes. The relocation process will allow for Town staff to access the pump stations throughout flood events if any problems were to occur. Allowing the Town to use its staff and resources on other high priority problems that may occur throughout the Town and shifting their focus from repairing each pump station upon current inevitable failure during a 100-year flood event. Water quality within the Town's surrounding environment will greatly improve with the relocation of the two pump stations. Sanitary sewer overflows within the two pump station service areas currently discharge untreated sewage into Old Field Swamp and surrounding environments, exposing species that inhabit these areas to water that contains harmful elements. Relocation of each pump station will protect animal and plant species within the Town, allowing all that are currently affected to remain healthy and prosper.

Along with relocation another level of flood protection will be provided at each pump station. Current operation components at each station are not protected by floodwaters and fail when submerged. Elevation of the pump stations will provide one layer of protection from floodwaters that surpass the 100-year flood level, however, each station will be equipped with stand-by generators that are elevated for extra protection. The pump station sites will also consist of new submersible pumps, wet well, valve vault emergency bypass connection, electrical, controls, security fencing, and site work to improve aesthetics. Vital components at the pump station will also be accessible by Town staff, allowing for regular maintenance to continue during flood events.

## 2.0 HISTORIC EVENTS

Hurricane Florence and Matthew have been the two major flood events that have caused the Happy Hills and North Walnut pump stations to fail. Both 100-year flood events have occurred within the last 5 years, not “100-years” apart. It is unknown as to how many storms of the “100-year” magnitude are to come in the future, but the Town of Fairmont wants to be prepared for the worst. Attached photographic evidence from Hurricane Florence reveals the devastating effects to each pump station, making them inoperable during these emergency conditions due to submersion in floodwaters. Currently the pump stations cannot be reached during flood events of the magnitude shown in the attached pictures from Hurricane Florence. The Town of Fairmont wants to have a proactive approach, not a reactive approach as the Town currently does. Community safety is of highest priority for the Town of Fairmont and this pump station relocation project will help to provide the community with a safe and reliable wastewater collection system, along with a cleaner environment.

**Figure 2.1 Happy Hills Pump Station During Hurricane Florence**



Above in **Figure 2.1** is a picture of the Happy Hills Pump Station completely covered in floodwaters from Hurricane Florence. The pump station was failing and inaccessible to Town Staff for an extended period of time. When Town Staff could finally access the pump station, majority of damage was already over. Gallons of wastewater had entered the environment at the pump station site and potential sanitary sewer overflows at other manhole locations.

**Figure 2.2 North Walnut Pump Station During Hurricane Florence**



Above in **Figure 2.2** is a photograph of the North Walnut Pump Station submerged in floodwaters left by Hurricane Florence. Although Town Staff could get minimal access to the pump station site, no repairs could be completed due to the station being under water. Customers tied to the station were not being served for an extended period of time, causing back up that can potentially overflow into homes and businesses in the service area.

### 3.0 PROJECT AND MAINTENANCE COSTS

The total combined project cost for the relocation of the Happy Hills and North Walnut pump stations is represented below in **Figure 3.1**. Combined annual maintenance cost for the two pump stations totals up to approximately \$8,750. The maintenance cost includes proper upkeep, testing, and expected repairs to be made at each pump station.

**Figure 3.1 Project and Maintenance Costs**

| Mitigation Activity     | Project Cost | Annual Maintenance Cost |
|-------------------------|--------------|-------------------------|
| Pump Station Relocation | \$2,752,650  | \$8,750                 |

The Golden LEAF Foundation provides economic relief to rural communities in North Carolina, encouraging growth and collaboration. Golden LEAF has already committed \$345,000 of funding to initiate improvements at these pump stations, but insufficient funding was available to provide an adequate long-term solution. Therefore, Golden LEAF funding has been provided to the Town of Fairmont to install back-up generators and raise electrical components at the pump station sites. While these steps are beneficial, they will not adequately protect the stations from future damage. A change in the scope of work will be needed to allocate the funding specifically for these two pump stations. If the request for change in scope of work is approved by the GLF, **Figure 3.2** below shows the amount of funding that will be needed to accompany the Golden LEAF Foundation’s contribution in order to provide the Town of Fairmont with two reliable pump stations for the community.

## **4.0 PROJECT USEFUL LIFE**

The 2009 FEMA BCA Reference Guide Project Useful Life Summary Table attached in **Appendix E**, states that a Pump Station project should have a standard useful life value of 50 years. Therefore, a standard useful life of 50 years was used for the Happy Hills and North Walnut pump stations, for calculations with the BCA Excel Tool. An export of the Benefit-Cost Analysis summary can be found in **Appendix B**.

---

## 5.0 SERVICE POPULATION

According to 2020 U.S. Census data, the Town of Fairmont's total population is 2,191. Fairmont is a disadvantaged community as the population is less than 3,000 and the per capita income is \$12,937 (based on data obtained from the NCOSBM website), which is approximately 36% of the National Average of \$35,672. Approximately 46% of households in the Town of Fairmont have a household income of below \$25,000 a year (information obtained from EJSscreen ACS Report). The North Walnut Pump Station directly serves approximately 48 people and the Happy Hill pump station serves approximately 120 people. Relocation of two pump stations to improve wastewater collection service for 168 people within the Town seems like a small percentage, but when considering the benefits this project provides to the Town of Fairmont, many more citizens will be positively impacted. Downstream of the pump stations are crop fields, livestock, homes, businesses, and other ecosystems that are collecting raw sewage water from flooding at these pump stations. Wastewater contains many harmful contaminants that are unhealthy for consumption by humans and animals, as well as detrimental to local wildlife habitats. Sanitary sewer overflows occur due to excessive flooding at each station, causing raw sewage to flow into parts of the community that may not necessarily be tied to the collection system. Relocation of the two pump stations will provide a cleaner and safer environment for all citizens within the Town of Fairmont. See attached sewer service area map in **Appendix F**.

## 6.0 EFFECTS OF FLOODING

### 6.1 Source of Flooding

The North Walnut and Happy Hills pump stations have experienced flooding from two major events in the last 5 years, Hurricane Florence in September of 2018 and Hurricane Matthew in October of 2016. At the time of each event, both pump stations were fully inundated with floodwaters and could not be accessed by Town staff. The pump stations were out of service for several days causing wastewater backup throughout the collection system. Floodwaters infiltrated each station, forcing pumps to process more water than designed to handle, and eventual failure due to flood water damage.

### 6.2 Historical Damages

Recurrence intervals were determined by most recent NOAA rainfall data from October 2016 and September 2018, attached in **Appendix D**. The data presented below in **Figure 6.1** is rainfall data for the Lumberton Area from NOAA Precipitation records. The City of Lumberton is located approximately 10 miles Northeast of the Town of Fairmont, sharing similar rainfall activity due to close proximity.

**Figure 6.1 Collection System Impact During Outages**

| Event  | Rainfall Duration (Days) | Rainfall (inches) | Wastewater Impact at North Walnut (days) | Wastewater Impact at Happy Hills (days) |
|--|--------------------------|-------------------|--|---|
| Hurricane Matthew (10/07/2016 - 10/09/2016)  | 2                        | 12.53             | 7  | 7                                       |
| Hurricane Florence (09/14/2018 - 09/16/2018) | 3                        | 17.06             | 7  | 7                                       |
| Outages (From Violations; 2020)              | N/A                      | N/A               | 4.5                                      | 4.5                                     |

### **6.3 Service Impacts**

Although these stations process relatively small amounts of flow, flooding at these pump stations cause major inflow and infiltration into the Town's sanitary sewer collection system. Due to the location of each station within the 100-year floodplain, there are large volumes of extraneous flow that enter the Town's collection system in this area during heavy rainfall. It is highly likely that this area is subject to frequent sanitary sewer overflows during heavy rain events due to the large amounts of extraneous flow which poses a significant environmental risk. Due to its close proximity, sanitary sewer overflows in the project area are likely to discharge untreated sewage into the nearby Old Field Swamp. However, as the Town has no way to access this outfall during heavy rain events, the Town is not able to document overflows and they often go unreported. These inflow and infiltration events cause unnecessary water to be processed at the wastewater treatment facility, negatively impacting the Town in multiple ways. Reducing discharge to the Fairmont Regional Wastewater Facility will allow the treatment plant to process flow from other areas, potentially allowing for growth in surrounding areas. Additionally, this inflow and infiltration contributes to sanitary sewer overflows downstream of the project area which has a negative impact on the environment and contributes to fines and penalties. These pump stations must be repaired after each destructive event, using up Town resources to fix a pump station that will inevitably fail in similar future situations. Valuable money and time currently spent to repair each pump station can be allocated for other needs within the Town's wastewater collection system upon relocation of the two pump stations. For these reasons, the relocation of these pump stations will provide a benefit to all residents of the Town of Fairmont.



## 7.0 RESULTS


Using the benefit-cost analysis tool provide by FEMA GO through Microsoft Excel, the table below shows the Benefit-Cost Ratio for the Pump Station Relocation Project. After all information required was input into the provided BCA Tool, the determined benefit-cost ratio is 1.68. **Figure 7.1** below shows a summary of total benefits and costs associated with the relocation of the Happy Hills and North Walnut Pump Stations for the Town of Fairmont.

**Figure 7.1 Pump Station Relocation Project Benefit-Cost Ratio**








| Project                 | Benefits    | Costs       | Benefit-Cost Ratio |
|-------------------------|-------------|-------------|--------------------|
| Pump Station Relocation | \$4,997,235 | \$2,977,785 | 1.68               |

The total benefits from the implementation of the pump station relocation project approximately outweigh the cost of the project by 1.7 times. Not only will the project provide an exceptional sewer collection service to the areas serviced by each pump station, but the Town of Fairmont will maintain a clean and healthy environment next time a flood event occurs.


## **APPENDIX A: PROJECT LAYOUT MAPS**




### Legend

-  Proposed Pump Station
-  Proposed Forcemain
-  Proposed Gravity Sewer
-  Existing Pump Stations
-  Forcemain
-  GravitySewer
-  100-yr Floodplain

## Sewer Pump Station Relocation and Flood Protection Project Happy Hills Pump Station Town of Fairmont, NC







### Legend

- Proposed Pump Station
- Existing Pump Station
- Proposed Forcemain
- Proposed Gravity Sewer
- Forcemain
- GravitySewer
- 100-yr Floodplain

## Sewer Pump Station Relocation and Flood Protection Project North Walnut Pump Station Town of Fairmont, NC

0 75 150 300  
 Feet

**APPENDIX B: BENEFIT-COST ANALYSIS  
TOOLKIT EXPORT**

**Project Summary**

| Mitigation Title                    | Hazard             | Benefits (B) | Costs (C)   | BCR (B/C) |
|-------------------------------------|--------------------|--------------|-------------|-----------|
| Elevation @ 34.4968000; -79.1142000 |                    |              |             |           |
| 79.1142000                          | FA - Riverine Floo | \$6,466,574  | \$2,188,686 | 2.95      |
|                                     | Total              | \$6,466,574  | \$2,188,686 | 2.95      |

**Property Configuration**

|                         |                                     |
|-------------------------|-------------------------------------|
| Property Title:         | Elevation @ 34.4968000; -79.1142000 |
| Property Location:      | 28340, Robeson, North Carolina      |
| Property Coordinates:   | 34.4968, -79.1142                   |
| Hazard Type:            | Riverine Flood                      |
| Mitigation Action Type: | Elevation                           |
| Property Type:          | Utilities                           |
| Analysis Method Type:   | Professional Expected Damages       |

**Cost Estimation**

Elevation @ 34.4968000; -79.1142000

|                              |                     |
|------------------------------|---------------------|
| Project Useful Life (years): | 50                  |
| Project Cost:                | \$2,070,000         |
| Number of Maintenance Years: | 50 Use Default: Yes |
| Annual Maintenance Cost:     | \$8,600             |

**Damage Analysis Parameters -**

**Damage Frequency Assessment**

Elevation @ 34.4968000; -79.1142000

|                             |                     |
|-----------------------------|---------------------|
| Year of Analysis Conducted: | 2021                |
| Year Property was Built:    | 1998                |
| Analysis Duration:          | 24 Use Default: Yes |

**Comments**

|             |   |
|-------------|---|
| Year Built: | Project includes two pump stations: North Walnut Pump Station was built in 2001 and Happy Hill Pump Station was built in 1988 |
|-------------|---|

**Utilities Properties**

Elevation @ 34.4968000; -79.1142000

|   |                       |
|---|-----------------------|
| Type of Service:                          | Wastewater            |
| Number of Customers Served:               | 1,600                 |
| Value of Unit of Service (\$/person/day): | \$58 Use Default: Yes |
| Total Value of Service Per Day (\$/day):  | \$92,800              |

**Comments**

|                             |   |
|-----------------------------|---|
| Number of Customers Served: | Relocation of each pump station not only affects customers in the pump station service areas, but also affect downstream customers. Total customers in the pump station service areas would total to approximately 168. However, flooding at these pump stations affect all customers within the system, which totals 1,600 customers. The flooding at the pump stations contributes to downstream incidents, including sewage backing up into customers homes and sanitary sewer overflows into yards. |
|-----------------------------|---|

**Professional Expected Damages Before Mitigation**

Elevation @ 34.4968000; -79.1142000

| Recurrence Interval (years) | Wastewater Impact (days) | Optional Damages or Replacement Component Category 3 (\$) | Volunteer Costs (\$) | Total Damages (\$) |   |   |           |
|-----------------------------|--------------------------|---|----------------------|--------------------|---|---|-----------|
| 2.5                         | 14                       | 41,000  | 65,500               | 0                  | 0 | 0 | 1,405,700 |

| Annualized Damages Before Mitigation |                          |  |                 |
|--------------------------------------|--------------------------|--|-----------------|
| Elevation @ 34.4968000; -79.1142000  |                          |  |                 |
| Annualized Recurrence                |                          |  |                 |
| Interval (years)                     | Wastewater Impact (days) | Optional Damages or Replacement Component Category 3 (\$/Year) | Volunteer Costs |
| 3                                    | 1,405,700                | 468,567  |                 |
| Sum Damages and Losses               |                          |  |                 |
|                                      | 1,405,700                | 468,567  |                 |

| Professional Expected Damages After Mitigation |                          |  |                 |       |   |   |   |
|--|--------------------------|--|-----------------|-------|---|---|---|
| Elevation @ 34.4968000; -79.1142000            |                          |  |                 |       |   |   |   |
| Recurrence Interval (years)                    | Wastewater Impact (days) | Optional Damages or Replacement Component Category 3 (\$/Year) | Volunteer Costs | Total |   |   |   |
| 2.5  | 0                        | 0  | 0               | 0     | 0 | 0 | 0 |

| Annualized Damages After Mitigation |                          |  |                 |
|-------------------------------------|--------------------------|--|-----------------|
| Elevation @ 34.4968000; -79.1142000 |                          |  |                 |
| Annualized Recurrence               |                          |  |                 |
| Interval (years)                    | Wastewater Impact (days) | Optional Damages or Replacement Component Category 3 (\$/Year) | Volunteer Costs |
| 2.5                                 | 0                        | 0  |                 |
| Sum Damages and Losses              |                          |  |                 |
|                                     | 0                        | 0  |                 |

| Benefits-Costs Summary                  |             |
|---|-------------|
| Elevation @ 34.4968000; -79.1142000     |             |
| Total Standard Mitigation Benefits:     | \$6,466,574 |
| Total Social Benefits:                  | \$0         |
| Total Mitigation Project Benefits:      | \$6,466,574 |
| Total Mitigation Project Cost:          | \$2,188,686 |
| Benefit Cost Ratio - Standard:          | 2.95        |
| Benefit Cost Ratio - Standard + Social: | 2.95        |


**APPENDIX C: FLOOD INSURANCE RATE  
MAPS**





|  |  |
|--|--|
|  | Without Base Flood Elevation (BFE)<br><i>Zone A, V, A99</i>                      |
|  | With BFE or Depth<br><i>Zone AE, AO, AH, VE, AR</i>                              |
|  | Regulatory Floodway  |
|  | 0.2% Annual Chance Flood Hazard  |
|  | Future Conditions 1% Annual Chance Flood Hazard <i>Zone X</i>                    |
|  | Areas Determined to be Outside the 0.2% Annual Chance Flood Hazard <i>Zone X</i> |
|  | Jurisdiction Boundary  |
|  | FIRM Panel Boundary  |

North Carolina State Plane Projection Feet (Zone 3200)  
Datum: NAD 1983 (Horizontal), NAVD 1988 (Vertical)



**FEMA National Flood Insurance Program**

**NATIONAL FLOOD INSURANCE PROGRAM**  
FLOOD INSURANCE RATE MAP

Panel(s): 9267, 9277

CONTAINS:  
COMMUNITY CID  
TOWN OF FAIRMONT 370205

Notice to User: The Map Number(s) shown below should be used when placing map orders; the Community Number(s) shown above should be used on insurance applications for the subject community.

SELECTED PANELS:

| MAP NUMBER  | EFFECTIVE DATE |
|-------------|----------------|
| 3710926700J | 1/19/2005      |
| 3710927700J | 1/19/2005      |



# FEMA: National Flood Insurance Program



Panel(s): 9267, 9277

**CONTAINS:**

|                  |            |
|------------------|------------|
| <b>COMMUNITY</b> | <b>CID</b> |
| TOWN OF FAIRMONT | 370205     |

**Notice to User:** The Map Number(s) shown below should be used when placing map orders; the Community Number(s) shown above should be used on insurance applications for the subject community.

**SELECTED PANELS:**

|                   |                       |
|-------------------|-----------------------|
| <b>MAP NUMBER</b> | <b>EFFECTIVE DATE</b> |
| 3710926700J       | 1/19/2005             |
| 3710927700J       | 1/19/2005             |

### NOTES TO USERS

This is an official FIRMette of a portion of the effective panels listed in the Title Block shown on Page 1. The information represented on this FIRMette was extracted from the effective digital flood hazard data available at <http://fris.nc.gov/fris>.

Base flood elevation data, floodway, nonencroachment widths, information on certain areas no in the Special Flood Hazard Areas protected by flood control structures, and other pertinent data are available in the Flood Insurance Study (FIS) available at <http://fris.nc.gov/fris>. Users should be aware that flood elevations shown on this FIRMette represent elevations rounded to one tenth of a foot (0.1') and should be utilized in conjunction with data available in the FIS.

### NOTES TO USERS

Base map information and geospatial data used to develop this FIRMette were obtained from various organizations, including the participating local community(ies), state and federal agencies, and/or other sources. The primary base for this FIRM is aerial imagery acquired by the State in 2010. Information and geospatial data supplied by the local community(ies) that met FEMA base map specifications were considered the preferred source for development of the base map.

See geospatial metadata for the associated digital FIRMette for additional information about base map preparation. Base map features shown on this FIRMette, such as corporate limits, are based on the most up-to-date data available at the time of publication. Changes in the corporate limits may have occurred since this map was published. Map users should consult the appropriate community official or website to verify current conditions of jurisdictional boundaries and base map features. This map may contain roads that were not considered in the hydraulic analysis of streams where no new hydraulic model was created during the production of this statewide format FIRM.

Flood elevations on this map are referenced to either or both the North American Vertical Datum of 1988 (NAVD 88) or National Geodetic Datum of 1929 (NGVD 29), and are labeled accordingly. These flood elevations must be compared to structure and ground elevations referenced to the same vertical datum. To obtain current elevation, description, and/or location information for bench marks shown on this map, or for information regarding conversion between NGVD 29 and NAVD 88, please contact the Information Services Branch of the National Geodetic Survey at (301) 713-3242, or visit its website at <http://www.ngs.noaa.gov/>.

### MORE INFORMATION

|   |   |
|---|---|
| Letters of Map Amendment (LOMA)                         | 1-877-336-2627<br><a href="http://msc.fema.gov/">http://msc.fema.gov/</a>                           |
| Letters of Map Revision (LOMR)                          | 919-715-5711<br><a href="http://www.ncfloodmaps.com">www.ncfloodmaps.com</a>                        |
| Flood Insurance Availability                            |   |
| North Carolina Division of Emergency Management (NCDEM) | 919-715-5711<br><a href="http://www.nccrimecontrol.org/nfip">http://www.nccrimecontrol.org/nfip</a> |
| National Flood Insurance Program (NFIP)                 | 1-877-638-6620<br><a href="http://www.fema.gov/business/nfip">http://www.fema.gov/business/nfip</a> |
| Questions about this FIRMette                           | 1-877-336-2627<br><a href="http://fema.gov">http://fema.gov</a>                                     |

### LEGEND

#### LEGEND

#### MAP REVISIONS


**There are no map revisions for the selected area.**





|  |  |
|--|--|
|  | Without Base Flood Elevation (BFE)<br><i>Zone A, V, A99</i>                      |
|  | With BFE or Depth<br><i>Zone AE, AO, AH, VE, AR</i>                              |
|  | Regulatory Floodway  |
|  | 0.2% Annual Chance Flood Hazard  |
|  | Future Conditions 1% Annual Chance Flood Hazard <i>Zone X</i>                    |
|  | Areas Determined to be Outside the 0.2% Annual Chance Flood Hazard <i>Zone X</i> |
|  | Jurisdiction Boundary  |
|  | FIRM Panel Boundary  |

North Carolina State Plane Projection Feet (Zone 3200)  
Datum: NAD 1983 (Horizontal), NAVD 1988 (Vertical)



N. Walnut PS Site

**FEMA National Flood Insurance Program**

**NATIONAL FLOOD INSURANCE PROGRAM**  
FLOOD INSURANCE RATE MAP

Panel(s):9267  
CONTAINS:  
COMMUNITY CID  
TOWN OF FAIRMONT 370205

Notice to User: The Map Number(s) shown below should be used when placing map orders; the Community Number(s) shown above should be used on insurance applications for the subject community.

SELECTED PANELS:  
MAP NUMBER EFFECTIVE DATE  
3710926700J 1/19/2005



# FEMA: National Flood Insurance Program



Panel(s):9267

**CONTAINS:**

|                  |            |
|------------------|------------|
| <b>COMMUNITY</b> | <b>CID</b> |
| TOWN OF FAIRMONT | 370205     |

**Notice to User: The Map Number(s) shown below should be used when placing map orders; the Community Number(s) shown above should be used on insurance applications for the subject community.**

**SELECTED PANELS:**

|                   |                       |
|-------------------|-----------------------|
| <b>MAP NUMBER</b> | <b>EFFECTIVE DATE</b> |
| 3710926700J       | 1/19/2005             |

### NOTES TO USERS

This is an official FIRMette of a portion of the effective panels listed in the Title Block shown on Page 1. The information represented on this FIRMette was extracted from the effective digital flood hazard data available at <http://fris.nc.gov/fris>.

Base flood elevation data, floodway, nonencroachment widths, information on certain areas no in the Special Flood Hazard Areas protected by flood control structures, and other pertinent data are available in the Flood Insurance Study (FIS) available at <http://fris.nc.gov/fris>. Users should be aware that flood elevations shown on this FIRMette represent elevations rounded to one tenth of a foot (0.1') and should be utilized in conjunction with data available in the FIS.

### NOTES TO USERS

Base map information and geospatial data used to develop this FIRMette were obtained from various organizations, including the participating local community(ies), state and federal agencies, and/or other sources. The primary base for this FIRM is aerial imagery acquired by the State in 2010. Information and geospatial data supplied by the local community(ies) that met FEMA base map specifications were considered the preferred source for development of the base map.

See geospatial metadata for the associated digital FIRMette for additional information about base map preparation. Base map features shown on this FIRMette, such as corporate limits, are based on the most up-to-date data available at the time of publication. Changes in the corporate limits may have occurred since this map was published. Map users should consult the appropriate community official or website to verify current conditions of jurisdictional boundaries and base map features. This map may contain roads that were not considered in the hydraulic analysis of streams where no new hydraulic model was created during the production of this statewide format FIRM.

Flood elevations on this map are referenced to either or both the North American Vertical Datum of 1988 (NAVD 88) or National Geodetic Datum of 1929 (NGVD 29), and are labeled accordingly. These flood elevations must be compared to structure and ground elevations referenced to the same vertical datum. To obtain current elevation, description, and/or location information for bench marks shown on this map, or for information regarding conversion between NGVD 29 and NAVD 88, please contact the Information Services Branch of the National Geodetic Survey at (301) 713-3242, or visit its website at <http://www.ngs.noaa.gov/>.

### MORE INFORMATION

|   |   |
|---|---|
| Letters of Map Amendment (LOMA)                         | 1-877-336-2627<br><a href="http://msc.fema.gov/">http://msc.fema.gov/</a>                           |
| Letters of Map Revision (LOMR)                          | 919-715-5711<br><a href="http://www.ncfloodmaps.com">www.ncfloodmaps.com</a>                        |
| Flood Insurance Availability                            |   |
| North Carolina Division of Emergency Management (NCDEM) | 919-715-5711<br><a href="http://www.nccrimecontrol.org/nfip">http://www.nccrimecontrol.org/nfip</a> |
| National Flood Insurance Program (NFIP)                 | 1-877-638-6620<br><a href="http://www.fema.gov/business/nfip">http://www.fema.gov/business/nfip</a> |
| Questions about this FIRMette                           | 1-877-336-2627<br><a href="http://fema.gov">http://fema.gov</a>                                     |

### LEGEND

#### LEGEND

#### MAP REVISIONS

**There are no map revisions for the selected area.**

**APPENDIX D: NOAA POINT  
PRECIPITATION FREQUENCY  
ESTIMATES AND DATA**



**NOAA Atlas 14, Volume 2, Version 3**  
**Location name: Fairmont, North Carolina, USA\***  
**Latitude: 34.4971°, Longitude: -79.1104°**  
**Elevation: 119.53 ft\*\***  
\* source: ESRI Maps  
\*\* source: USGS



**POINT PRECIPITATION FREQUENCY ESTIMATES**

G.M. Bonnin, D. Martin, B. Lin, T. Parzybok, M. Yekta, and D. Riley

NOAA, National Weather Service, Silver Spring, Maryland

[PF tabular](#) | [PF graphical](#) | [Maps & aeriels](#)

**PF tabular**

| <b>PDS-based point precipitation frequency estimates with 90% confidence intervals (in inches)<sup>1</sup></b> |  |                               |                               |                               |                               |                               |                               |                              |                             |                             |
|--|--|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|------------------------------|-----------------------------|-----------------------------|
| <b>Duration</b>  | <b>Average recurrence interval (years)</b> |                               |                               |                               |                               |                               |                               |                              |                             |                             |
|  | <b>1</b>                                   | <b>2</b>                      | <b>5</b>                      | <b>10</b>                     | <b>25</b>                     | <b>50</b>                     | <b>100</b>                    | <b>200</b>                   | <b>500</b>                  | <b>1000</b>                 |
| <b>5-min</b>   | <b>0.443</b><br>(0.406-0.484)              | <b>0.523</b><br>(0.480-0.571) | <b>0.612</b><br>(0.561-0.670) | <b>0.681</b><br>(0.622-0.743) | <b>0.766</b><br>(0.697-0.835) | <b>0.830</b><br>(0.753-0.903) | <b>0.893</b><br>(0.805-0.970) | <b>0.953</b><br>(0.855-1.04) | <b>1.03</b><br>(0.917-1.12) | <b>1.09</b><br>(0.964-1.19) |
| <b>10-min</b>  | <b>0.707</b><br>(0.649-0.774)              | <b>0.836</b><br>(0.767-0.914) | <b>0.981</b><br>(0.898-1.07)  | <b>1.09</b><br>(0.995-1.19)   | <b>1.22</b><br>(1.11-1.33)    | <b>1.32</b><br>(1.20-1.44)    | <b>1.42</b><br>(1.28-1.54)    | <b>1.51</b><br>(1.36-1.64)   | <b>1.63</b><br>(1.45-1.77)  | <b>1.72</b><br>(1.52-1.87)  |
| <b>15-min</b>  | <b>0.884</b><br>(0.811-0.967)              | <b>1.05</b><br>(0.965-1.15)   | <b>1.24</b><br>(1.14-1.36)    | <b>1.38</b><br>(1.26-1.50)    | <b>1.55</b><br>(1.41-1.69)    | <b>1.67</b><br>(1.52-1.82)    | <b>1.79</b><br>(1.62-1.95)    | <b>1.91</b><br>(1.71-2.07)   | <b>2.05</b><br>(1.83-2.23)  | <b>2.16</b><br>(1.91-2.35)  |
| <b>30-min</b>  | <b>1.21</b><br>(1.11-1.33)                 | <b>1.45</b><br>(1.33-1.59)    | <b>1.76</b><br>(1.61-1.93)    | <b>2.00</b><br>(1.82-2.18)    | <b>2.29</b><br>(2.09-2.50)    | <b>2.52</b><br>(2.29-2.74)    | <b>2.75</b><br>(2.48-2.99)    | <b>2.97</b><br>(2.66-3.23)   | <b>3.27</b><br>(2.90-3.55)  | <b>3.50</b><br>(3.09-3.81)  |
| <b>60-min</b>  | <b>1.51</b><br>(1.39-1.65)                 | <b>1.82</b><br>(1.67-1.99)    | <b>2.26</b><br>(2.07-2.47)    | <b>2.60</b><br>(2.38-2.84)    | <b>3.05</b><br>(2.78-3.33)    | <b>3.42</b><br>(3.10-3.72)    | <b>3.78</b><br>(3.41-4.11)    | <b>4.16</b><br>(3.73-4.52)   | <b>4.68</b><br>(4.17-5.10)  | <b>5.10</b><br>(4.51-5.56)  |
| <b>2-hr</b>  | <b>1.75</b><br>(1.60-1.94)                 | <b>2.12</b><br>(1.94-2.34)    | <b>2.69</b><br>(2.45-2.96)    | <b>3.14</b><br>(2.85-3.45)    | <b>3.76</b><br>(3.40-4.14)    | <b>4.27</b><br>(3.85-4.69)    | <b>4.81</b><br>(4.31-5.28)    | <b>5.38</b><br>(4.79-5.90)   | <b>6.18</b><br>(5.44-6.78)  | <b>6.83</b><br>(5.97-7.50)  |
| <b>3-hr</b>  | <b>1.86</b><br>(1.69-2.07)                 | <b>2.25</b><br>(2.04-2.50)    | <b>2.86</b><br>(2.60-3.17)    | <b>3.36</b><br>(3.05-3.73)    | <b>4.08</b><br>(3.68-4.51)    | <b>4.69</b><br>(4.19-5.18)    | <b>5.33</b><br>(4.74-5.89)    | <b>6.03</b><br>(5.31-6.64)   | <b>7.05</b><br>(6.13-7.77)  | <b>7.90</b><br>(6.80-8.70)  |
| <b>6-hr</b>  | <b>2.20</b><br>(2.00-2.46)                 | <b>2.67</b><br>(2.42-2.97)    | <b>3.39</b><br>(3.08-3.77)    | <b>4.00</b><br>(3.61-4.44)    | <b>4.87</b><br>(4.37-5.39)    | <b>5.61</b><br>(4.99-6.19)    | <b>6.41</b><br>(5.66-7.06)    | <b>7.27</b><br>(6.36-8.00)   | <b>8.54</b><br>(7.38-9.39)  | <b>9.59</b><br>(8.20-10.5)  |
| <b>12-hr</b>   | <b>2.59</b><br>(2.34-2.90)                 | <b>3.13</b><br>(2.82-3.51)    | <b>4.00</b><br>(3.60-4.48)    | <b>4.74</b><br>(4.25-5.29)    | <b>5.81</b><br>(5.18-6.47)    | <b>6.74</b><br>(5.96-7.48)    | <b>7.74</b><br>(6.78-8.58)    | <b>8.84</b><br>(7.67-9.78)   | <b>10.5</b><br>(8.95-11.6)  | <b>11.9</b><br>(10.0-13.1)  |
| <b>24-hr</b>   | <b>3.03</b><br>(2.80-3.30)                 | <b>3.68</b><br>(3.40-4.02)    | <b>4.74</b><br>(4.36-5.16)    | <b>5.61</b><br>(5.15-6.11)    | <b>6.87</b><br>(6.27-7.47)    | <b>7.93</b><br>(7.19-8.62)    | <b>9.07</b><br>(8.17-9.87)    | <b>10.3</b><br>(9.21-11.2)   | <b>12.1</b><br>(10.7-13.2)  | <b>13.6</b><br>(11.9-14.9)  |
| <b>2-day</b>   | <b>3.54</b><br>(3.27-3.86)                 | <b>4.29</b><br>(3.96-4.68)    | <b>5.47</b><br>(5.04-5.96)    | <b>6.45</b><br>(5.93-7.02)    | <b>7.85</b><br>(7.17-8.55)    | <b>9.02</b><br>(8.19-9.82)    | <b>10.3</b><br>(9.27-11.2)    | <b>11.6</b><br>(10.4-12.7)   | <b>13.6</b><br>(12.0-14.9)  | <b>15.2</b><br>(13.3-16.7)  |
| <b>3-day</b>   | <b>3.77</b><br>(3.49-4.09)                 | <b>4.56</b><br>(4.22-4.94)    | <b>5.78</b><br>(5.35-6.26)    | <b>6.78</b><br>(6.26-7.35)    | <b>8.22</b><br>(7.54-8.90)    | <b>9.40</b><br>(8.58-10.2)    | <b>10.7</b><br>(9.67-11.6)    | <b>12.0</b><br>(10.8-13.1)   | <b>14.0</b><br>(12.4-15.2)  | <b>15.6</b><br>(13.7-17.0)  |
| <b>4-day</b>   | <b>4.00</b><br>(3.72-4.32)                 | <b>4.83</b><br>(4.49-5.20)    | <b>6.09</b><br>(5.65-6.57)    | <b>7.12</b><br>(6.59-7.67)    | <b>8.58</b><br>(7.90-9.25)    | <b>9.78</b><br>(8.97-10.6)    | <b>11.1</b><br>(10.1-11.9)    | <b>12.4</b><br>(11.2-13.4)   | <b>14.4</b><br>(12.8-15.6)  | <b>16.0</b><br>(14.2-17.4)  |
| <b>7-day</b>   | <b>4.66</b><br>(4.34-5.01)                 | <b>5.61</b><br>(5.22-6.03)    | <b>7.00</b><br>(6.51-7.54)    | <b>8.12</b><br>(7.53-8.73)    | <b>9.69</b><br>(8.95-10.4)    | <b>11.0</b><br>(10.1-11.8)    | <b>12.3</b><br>(11.2-13.2)    | <b>13.7</b><br>(12.4-14.8)   | <b>15.7</b><br>(14.1-17.0)  | <b>17.3</b><br>(15.4-18.8)  |
| <b>10-day</b>  | <b>5.36</b><br>(5.02-5.73)                 | <b>6.42</b><br>(6.01-6.86)    | <b>7.89</b><br>(7.37-8.43)    | <b>9.05</b><br>(8.45-9.67)    | <b>10.6</b><br>(9.90-11.4)    | <b>11.9</b><br>(11.0-12.8)    | <b>13.3</b><br>(12.2-14.2)    | <b>14.6</b><br>(13.4-15.7)   | <b>16.6</b><br>(15.0-17.9)  | <b>18.1</b><br>(16.3-19.6)  |
| <b>20-day</b>  | <b>7.20</b><br>(6.79-7.65)                 | <b>8.58</b><br>(8.09-9.11)    | <b>10.4</b><br>(9.77-11.0)    | <b>11.8</b><br>(11.1-12.5)    | <b>13.7</b><br>(12.9-14.6)    | <b>15.3</b><br>(14.3-16.2)    | <b>16.9</b><br>(15.7-17.9)    | <b>18.5</b><br>(17.1-19.7)   | <b>20.7</b><br>(19.0-22.2)  | <b>22.5</b><br>(20.5-24.2)  |
| <b>30-day</b>  | <b>8.97</b><br>(8.50-9.49)                 | <b>10.6</b><br>(10.1-11.3)    | <b>12.6</b><br>(12.0-13.4)    | <b>14.2</b><br>(13.4-15.0)    | <b>16.3</b><br>(15.3-17.2)    | <b>17.9</b><br>(16.8-18.9)    | <b>19.5</b><br>(18.2-20.7)    | <b>21.1</b><br>(19.7-22.5)   | <b>23.3</b><br>(21.6-24.9)  | <b>25.1</b><br>(23.1-26.8)  |
| <b>45-day</b>  | <b>11.3</b><br>(10.7-11.9)                 | <b>13.3</b><br>(12.6-14.0)    | <b>15.6</b><br>(14.8-16.4)    | <b>17.3</b><br>(16.4-18.2)    | <b>19.6</b><br>(18.5-20.7)    | <b>21.4</b><br>(20.1-22.6)    | <b>23.2</b><br>(21.7-24.5)    | <b>24.9</b><br>(23.3-26.4)   | <b>27.3</b><br>(25.4-29.0)  | <b>29.1</b><br>(26.9-31.0)  |
| <b>60-day</b>  | <b>13.5</b><br>(12.8-14.2)                 | <b>15.9</b><br>(15.1-16.7)    | <b>18.4</b><br>(17.5-19.4)    | <b>20.4</b><br>(19.3-21.4)    | <b>22.9</b><br>(21.6-24.0)    | <b>24.8</b><br>(23.4-26.1)    | <b>26.6</b><br>(25.1-28.1)    | <b>28.5</b><br>(26.7-30.1)   | <b>30.9</b><br>(28.8-32.7)  | <b>32.7</b><br>(30.4-34.7)  |

<sup>1</sup> Precipitation frequency (PF) estimates in this table are based on frequency analysis of partial duration series (PDS). Numbers in parenthesis are PF estimates at lower and upper bounds of the 90% confidence interval. The probability that precipitation frequency estimates (for a given duration and average recurrence interval) will be greater than the upper bound (or less than the lower bound) is 5%. Estimates at upper bounds are not checked against probable maximum precipitation (PMP) estimates and may be higher than currently valid PMP values. Please refer to NOAA Atlas 14 document for more information.





[Back to Top](#)

**PF graphical**



### PDS-based depth-duration-frequency (DDF) curves


Latitude: 34.4971°, Longitude: -79.1104°



[Back to Top](#)

## Maps & aerials


Small scale terrain



Large scale terrain




Large scale map



Large scale aerial





[Back to Top](#)

---

[US Department of Commerce](#)  
[National Oceanic and Atmospheric Administration](#)  
[National Weather Service](#)  
[National Water Center](#)  
1325 East West Highway  
Silver Spring, MD 20910  
Questions?: [HDSC.Questions@noaa.gov](mailto:HDSC.Questions@noaa.gov)

[Disclaimer](#)

## Climatological Data for Lumberton Area, NC (ThreadEx) - October 2016

| Date           | Temperature |         |         |           | HDD | CDD | Precipitation |
|----------------|-------------|---------|---------|-----------|-----|-----|---------------|
|                | Maximum     | Minimum | Average | Departure |     |     |               |
| 2016-10-01     | 86          | 59      | 72.5    | 2.7       | 0   | 8   | T             |
| 2016-10-02     | 84          | 60      | 72.0    | 2.6       | 0   | 7   | 0.00          |
| 2016-10-03     | 84          | 57      | 70.5    | 1.4       | 0   | 6   | 0.00          |
| 2016-10-04     | 79          | 64      | 71.5    | 2.8       | 0   | 7   | 0.00          |
| 2016-10-05     | 76          | 63      | 69.5    | 1.2       | 0   | 5   | 0.00          |
| 2016-10-06     | 73          | 62      | 67.5    | -0.5      | 0   | 3   | 0.00          |
| 2016-10-07     | 83          | 67      | 75.0    | 7.4       | 0   | 10  | 0.22          |
| 2016-10-08     | 75          | M       | M       | M         | M   | M   | 12.53         |
| 2016-10-09     | M           | M       | M       | M         | M   | M   | 0.02          |
| 2016-10-10     | M           | M       | M       | M         | M   | M   | M             |
| 2016-10-11     | 75          | 56      | 65.5    | -0.6      | 0   | 1   | 0.00          |
| 2016-10-12     | 79          | 54      | 66.5    | 0.8       | 0   | 2   | 0.00          |
| 2016-10-13     | 82          | 53      | 67.5    | 2.2       | 0   | 3   | 0.00          |
| 2016-10-14     | 76          | 59      | 67.5    | 2.6       | 0   | 3   | 0.00          |
| 2016-10-15     | 75          | 56      | 65.5    | 1.0       | 0   | 1   | 0.00          |
| 2016-10-16     | 81          | 54      | 67.5    | 3.3       | 0   | 3   | 0.00          |
| 2016-10-17     | 83          | 55      | 69.0    | 5.2       | 0   | 4   | 0.00          |
| 2016-10-18     | M           | M       | M       | M         | M   | M   | 0.00          |
| 2016-10-19     | M           | M       | M       | M         | M   | M   | 0.00          |
| 2016-10-20     | M           | M       | M       | M         | M   | M   | 0.00          |
| 2016-10-21     | 83          | 58      | 70.5    | 8.2       | 0   | 6   | M             |
| 2016-10-22     | 66          | 43      | 54.5    | -7.4      | 10  | 0   | 0.00          |
| 2016-10-23     | 71          | 38      | 54.5    | -7.0      | 10  | 0   | 0.00          |
| 2016-10-24     | 81          | 46      | 63.5    | 2.3       | 1   | 0   | 0.00          |
| 2016-10-25     | 70          | 45      | 57.5    | -3.3      | 7   | 0   | 0.00          |
| 2016-10-26     | 73          | 40      | 56.5    | -4.0      | 8   | 0   | 0.00          |
| 2016-10-27     | 79          | 50      | 64.5    | 4.4       | 0   | 0   | 0.00          |
| 2016-10-28     | 82          | 58      | 70.0    | 10.2      | 0   | 5   | 0.00          |
| 2016-10-29     | 81          | 48      | 64.5    | 5.1       | 0   | 0   | 0.00          |
| 2016-10-30     | 85          | 54      | 69.5    | 10.4      | 0   | 5   | 0.00          |
| 2016-10-31     | 80          | 53      | 66.5    | 7.8       | 0   | 2   | 0.00          |
| <b>Sum</b>     | 2042        | 1352    | -       | -         | 36  | 81  | 12.77         |
| <b>Average</b> | 78.5        | 54.1    | 66.4    | 2.2       | -   | -   | -             |
| <b>Normal</b>  | 75.9        | 52.5    | 64.2    | -         | 110 | 85  | 2.29          |

**Observations for each day cover the 24 hours ending  
at the time given below (Local Standard Time).**

Max Temperature : midnight

Min Temperature : midnight

Precipitation : midnight

## Climatological Data for Lumberton Area, NC (ThreadEx) - September 2018

| Date           | Temperature |         |         |           | HDD | CDD | Precipitation |
|----------------|-------------|---------|---------|-----------|-----|-----|---------------|
|                | Maximum     | Minimum | Average | Departure |     |     |               |
| 2018-09-01     | 94          | 71      | 82.5    | 4.5       | 0   | 18  | 0.00          |
| 2018-09-02     | 95          | 72      | 83.5    | 5.7       | 0   | 19  | 0.00          |
| 2018-09-03     | 94          | 70      | 82.0    | 4.4       | 0   | 17  | 0.00          |
| 2018-09-04     | 94          | 71      | 82.5    | 5.1       | 0   | 18  | 0.00          |
| 2018-09-05     | 94          | 72      | 83.0    | 5.8       | 0   | 18  | 0.00          |
| 2018-09-06     | 94          | 69      | 81.5    | 4.5       | 0   | 17  | 0.00          |
| 2018-09-07     | 95          | 68      | 81.5    | 4.7       | 0   | 17  | 0.00          |
| 2018-09-08     | 94          | 69      | 81.5    | 4.9       | 0   | 17  | 0.00          |
| 2018-09-09     | 94          | 69      | 81.5    | 5.1       | 0   | 17  | 0.00          |
| 2018-09-10     | 94          | 69      | 81.5    | 5.4       | 0   | 17  | T             |
| 2018-09-11     | 94          | 69      | 81.5    | 5.6       | 0   | 17  | 0.13          |
| 2018-09-12     | 94          | 73      | 83.5    | 7.8       | 0   | 19  | T             |
| 2018-09-13     | 88          | 72      | 80.0    | 4.6       | 0   | 15  | 0.36          |
| 2018-09-14     | 80          | 74      | 77.0    | 1.9       | 0   | 12  | 4.57          |
| 2018-09-15     | 76          | 74      | 75.0    | 0.1       | 0   | 10  | 10.95         |
| 2018-09-16     | 78          | 74      | 76.0    | 1.4       | 0   | 11  | 1.54          |
| 2018-09-17     | 89          | 75      | 82.0    | 7.7       | 0   | 17  | 0.01          |
| 2018-09-18     | 91          | 73      | 82.0    | 8.0       | 0   | 17  | 0.01          |
| 2018-09-19     | 92          | 71      | 81.5    | 7.8       | 0   | 17  | 0.00          |
| 2018-09-20     | 91          | 68      | 79.5    | 6.1       | 0   | 15  | 0.00          |
| 2018-09-21     | 86          | 69      | 77.5    | 4.4       | 0   | 13  | 0.00          |
| 2018-09-22     | 89          | 66      | 77.5    | 4.7       | 0   | 13  | 0.00          |
| 2018-09-23     | 88          | 66      | 77.0    | 4.5       | 0   | 12  | 0.00          |
| 2018-09-24     | 79          | 69      | 74.0    | 1.8       | 0   | 9   | 0.00          |
| 2018-09-25     | 90          | 71      | 80.5    | 8.6       | 0   | 16  | 0.00          |
| 2018-09-26     | 91          | 68      | 79.5    | 8.0       | 0   | 15  | 0.21          |
| 2018-09-27     | 90          | 71      | 80.5    | 9.3       | 0   | 16  | 0.93          |
| 2018-09-28     | 89          | 71      | 80.0    | 9.2       | 0   | 15  | 0.29          |
| 2018-09-29     | 87          | 72      | 79.5    | 9.0       | 0   | 15  | 0.00          |
| 2018-09-30     | 84          | 63      | 73.5    | 3.4       | 0   | 9   | 0.00          |
| <b>Sum</b>     | 2688        | 2109    | -       | -         | 0   | 458 | 19.00         |
| <b>Average</b> | 89.6        | 70.3    | 80.0    | 5.5       | -   | -   | -             |
| <b>Normal</b>  | 84.2        | 64.8    | 74.5    | -         | 7   | 292 | 4.93          |

**Observations for each day cover the 24 hours ending  
at the time given below (Local Standard Time).**

Max Temperature : midnight

Min Temperature : midnight

Precipitation : midnight

**APPENDIX E: FEMA 2009 BCA  
REFERENCE GUIDE - PROJECT USEFUL  
LIFE TABLE**

APPENDIX D  
Project Useful Life Summary

| Project Type  | Useful Life (years) |   | Comment   |
|---|---------------------|---|---|
|   | Standard Value      | Acceptable Limits<br>(documentation required) |   |
| <b>Acquisition/Relocation</b>   |                     |   |   |
| All Structures  | 100                 | 100   |   |
| <b>Elevation</b>  |                     |   |   |
| Residential Building  | 30                  | 30–50   |   |
| Non-Residential Building  | 25                  | 25–50   |   |
| Public Building   | 50                  | 50–100  |   |
| Historic Buildings  | 50                  | 50–100  |   |
| <b>Structural/Non-Structural Building Project</b>                               |                     |   |   |
| Residential Building Retrofit   | 30                  | 30  |   |
| Non-Residential Building Retrofit   | 25                  | 25–50   |   |
| Public Building Retrofit  | 50                  | 50–100  |   |
| Historic Building Retrofit  | 50                  | 50–100  |   |
| Roof Diaphragm Retrofit   | 30                  | 30  | Roof hardening and roof clips   |
| Tornado Safe Room – Residential   | 30                  | 30  |   |
| Tornado Safe Room – Community   | 30                  | 30–50   | Retrofit or small community safe room<br>≤ 16 people (30 yr), New (50 yr)               |
| Non-Structural Building Elements  | 30                  | 30  | Ceilings, electrical cabinets, generators, parapet walls, or chimneys                   |
| Non-Structural Major Equipment  | 15                  | 15–30   | Elevators, HVAC, sprinklers   |
| Non-Structural Minor Equipment  | 5                   | 5–20  | Generic contents, racks, shelves  |
| <b>Infrastructure Projects</b>  |                     |   |   |
| Major Infrastructure (minor localized flood reduction projects)                 | 50                  | 35–100  |   |
| Concrete Infrastructure, Flood Walls, Roads, Bridges, Major Drainage System     | 50                  | 35–50   |   |
| Culverts (concrete, PVC, CMP, HDPE, etc.)                                       | 30                  | 25–50   | Culvert <b>with</b> end treatment (i.e., wing walls, end sections, head walls, etc.)    |
|   | 10                  | 5–20  | Culvert <b>without</b> end treatment (i.e., wing walls, end sections, head walls, etc.) |
| Pump Stations, Substations, Wastewater Systems, or Equipment Such as Generators | 50                  | 50  | Structures  |
|   | 5                   | 5–30  | Equipment   |
| Hurricane Storm Shutters  | 15                  | 15–30   | Depends on type of storm shutter  |
| Utility Mitigation Projects   | 50                  | 50–100  | Major (power lines, cable, hardening gas, water, sewer lines, etc.)                     |
|   | 5                   | 5–30  | Minor (backflow valves, downspout disconnect, etc.)                                     |


APPENDIX D  
Project Useful Life Summary

| Project Type                               | Useful Life (years) |   | Comment  |
|--|---------------------|---|--|
|  | Standard Value      | Acceptable Limits<br>(documentation required) |  |
| <b>Miscellaneous Equipment Projects</b>    |                     |   |  |
| Equipment Purchases                        | 2                   | 2–10  | Small, portable equipment (e.g., computer)               |
|  | 30                  | 5–30  | Heavy equipment  |
| <b>Wildfire Mitigation Projects</b>        |                     |   |  |
| Defensible Space/Hazardous Fuels Reduction | 4                   | 2–4   | Brush – Depends on drought conditions                    |
| Vegetation Management                      | 1                   | 1   | Grass – Depends on geographic location and precipitation |
|  | 20                  | 3–20  | Forest canopy – Must be maintained every 3 years         |
| Ignition-Resistant Construction            | 10                  | 10–30   | Depends on type of construction and materials used       |

**APPENDIX F: PUMP STATION SERVICE  
AREA MAP**



**Pump Station Service Area Map**  
**Town of Fairmont**  
**Robeson County, NC**





**APPENDIX G: HISTORIC PHOTOS OF DAMAGE  
AT PUMP STATION SITES**

**Town of Fairmont  
Pump Station Photos**



*Happy Hill Pump Station – The flooded pump station is seen in the background following Hurricane Florence with no access to the station, located near the utility pole in center of picture*



**Town of Fairmont  
Pump Station Photos**



*Happy Hill Pump Station – Leaves on the fence show that the pump station was thoroughly submerged during hurricane / Note location of utility pole for reference to previous photo*



**Town of Fairmont  
Pump Station Photos**



*N. Walnut Street pump station site during Hurricane Florence flooding / Note station on left of highway and site completely underwater, days following Hurricane Florence*

**Town of Fairmont  
Pump Station Photos**



*N. Walnut Street pump station site with leaves and debris in the fence that show the water level during hurricane flooding*



**APPENDIX H: HAPPY HILL PUMP STATION  
RECORD DRAWINGS**



1005.4 EXTRA

19

# COUNTY OF ROBESON

NORTH CAROLINA

## FY 90 COMMUNITY DEVELOPMENT PROJECT

### HAPPY HILL REVITALIZATION

### 1992

CHAIRMAN: BOBBY DEAN LOCKLEAR

COMMISSIONERS:

BILLY S. BRITT      SAMMY COX      JOHNNY HUNT  
 LUTHER SANDERSON      NOAH WOODS  
 COMMUNITY DEVELOPMENT ADMINISTRATOR:  
 TOWN OF FAIRMONT - SCOTT DADSON

The  
**Wooten**  
 Company


AS BUILT DRAWINGS: ~~X~~  
 DATED 1-31-94  
 By: Noel Kinsey  
 By: Ben Hill

ENGINEERING - PLANNING - ARCHITECTURE  
 RALEIGH, N. C. - GREENVILLE, N. C.




#### INDEX TO DRAWINGS

- COVER / INDEX
- LEESVILLE ROAD GRAVITY SEWER AND FORCE MAIN
- GRIFFIN STREET IMPROVEMENTS
- PUMPING STATION AND RELATED WORK
- MISCELLANEOUS DETAILS AND ROADWAY IMPROVEMENT DETAILS

FND:



Total Quantities:  
 WATER Sewers = 9 EA.  
 Sewer Sewers = 20 EA.  
 Demolition - 1-31-94 = 6 EA.  
 Manholes = 148-29.04  
 (15) Asphalt Surface Lane = 1288.1 5.4 In. Patch  
 (14) Curbs = ABC Stone = 1350 3.4 " "











SHEET NO. 1 OF 5 SHEETS



PUMP STATION ELEVATIONS SCHEDULE

| PUMP STA. I.D.              | WET WELL DIAMETER (FT.) | CAPACITY (GPM) | T.D.H. (FT.) | MOTOR (HP) | TOP OF STATION ELEV. (FT) | BOTTOM OF STATION ELEV. (FT) | FINISH GRADE (FT) | LOW ALARM ELEV. (FT) | PUMP OFF ELEVATION (FT) | 1st PUMP ON ELEV. (FT) | 2nd PUMP ON ELEV. (FT) | HI. WATER ALARM ELEV. (FT) | VENT ELEVATION (FT) | ' INV. IN ELEVATION (FT) |
|-----------------------------|-------------------------|----------------|--------------|------------|---------------------------|------------------------------|-------------------|----------------------|-------------------------|------------------------|------------------------|----------------------------|---------------------|--------------------------|
| BASE BID PUMP STA. LOCATION | 6                       | 100            | 25           | 3.0        | 97.50                     | 84.0                         | 97.0              | 87.00                | 87.50                   | 88.50                  | 90.50                  | 90.50                      | 97.9                | 90.50                    |



REVISIONS

PROJECT NO. 2650-A

DATE: JAN. 1992

SCALE: AS SHOWN

DES. BY: JK

DWN. BY: JK

CHK'D BY: JK

APRIL 8, 1993

MAY 18, 1993

COUNTY OF ROBESON NORTH CAROLINA

COMMUNITY DEVELOPMENT PROJECT

PUMPING STATION AND RELATED WORK

**The Wooten Company**

ENGINEERING

PLANNING

ARCHITECTURE

RALEIGH, N.C.

GREENVILLE, N.C.

SINCE 1936

SHEET NO. 4

OF 5 SHEETS